

## **ARGILE LAQUE SATINEE EXTERIEURE**

Description: "ARGILE laque satinée extérieure" is an acrylic water based paint, flexible and microporous, with a smart decorative aspect. Odourless, washable, it is suitable for all wooden works.

Destination: surfaces like woodwork, doors, windows, furniture, on already painted surfaces or not, specially for outside use, but can be also used for inside woodwork.

Qualities:

- *flexible*
- *microporous*
- smooth effect, high decorative appearance.
- easy to use
- Odourless

VOC: - Limit value for this product (cat A/d) : 130 g/l. This product contains max 60 g/l of VOC.

### **Characteristics**

Appearance: satin, smooth finis

Shine: roughly 30 % (at 60°)

Destination: outside

Application / Painting: brush  
spray gun  
roller (lacquer roller, roller with short bristles, polyamide textured 6mm roller)

Density: 1.2

Coverage: 8-10 m<sup>2</sup> per liter, depending on surface

Drying time at 20°C: touch dry after 2 hours, re-coat after 4 hours

Washability: washable and wipeable

Conditions of painting: -air and surface temperature between 10°C and 25°C  
-relative humidity: max 80%. Humidity of the wood : max 15 %

Thinners / Dilution: ready to use – dilute with water if applying with spray gun (5-10%)

To clean tools: water

Colours: 128 colours

Availability: 0.75, 2.5 and 5 liters cans

## **Instructions for use**

### Preparation of surfaces:

The state and the preparation of surfaces should conform to professional uses specifications (DTU 59-1 in France).

"ARGILE laque satinée extérieure" is to be used after the following preparations: cleaning, degreasing, sand-papering... on the following interior and exterior surfaces:

- New non coated wood : sand by hand , clean.
- Non coated wood with spots, exuding tannin or resin, apply a specified primer, or a solvent based primer.
- Hard non coated wood : sand-paper, clean, and apply one first coat of "ARGILE primaire universel"
- Tender non coated wood : sand-paper, clean, then apply one first coat of "ARGILE laque satinée extérieure" diluted with water (5-10 % maximum)
- Greasy wood : dry with degreasing liquid.
- On painted wood with ancient varnish, wood stain, satin or glossy paint, check the adherence of the old coating, clean and then sand-paper thoroughly, apply one coat of "Argile primaire universel"
- On derivatives of wood (melamine, laminated wood...), clean and sand-paper, apply one coat of "Argile primaire universel"
- For furniture, remove all traces of polish or wax, sand-paper it thoroughly and scour off any old varnish. Then apply a coat of "ARGILE primaire universel", followed by two coats of "ARGILE Laque Satinée Extérieure"
- On other hard or difficult substrates, like plastic, PVC , apply first one coat of "ARGILE primaire universel"

## **Application**

Stir well manually before using the product

Apply two coats of "ARGILE laque satinée Extérieure" with brush, spray gun or roller

On smooth surfaces, those are perfectly prepared use a polyamide textured 6mm roller. On other surfaces, use a polyamide textured 6-8mm textured roller

Using a brush will obtain a taut appearance

When using a spray gun, dilute the product with water by 5-10%

## **Colors**

Outside, except in protected or not hardly exposed areas, we recommend to avoid the use of the following colors : T 511, T 513, T 521, T 531, T 532, T 541, T 542 .

### **Upkeep/Maintenance**

"ARGILE laque satinée extérieure" can be cleaned with a warm sponge. Avoid aggressive scrubbing. Use soft detergents if necessary.

### **Health and Safety**

Keep out of reach of children. Use only in well ventilated areas.