

ARGILE LAQUE SATINEE INTERIEURE

Description: "ARGILE laque satinée intérieure" is an acrylic-polyurethane water based paint, with a smart decorative aspect. Odourless, washable and resistant, it is suitable for all interior works.

Destination: surfaces like woodwork, walls, ceiling, doors, windows, furniture, inside use, on already painted surfaces or not. "ARGILE laque satinée intérieure" is washable, wipeable, and can be used in places such as bathrooms kitchens etc.

Qualities:

- *good opacity*
- *good resistance and durability of aspect and colours*
- smooth effect, high decorative appearance.
- easy to use
- Odourless

VOC: - Limit value for this product (cat A/a) : 30 g/l. This product contains max 30 g/l of VOC.

Characteristics

Appearance: silky-smooth finish, taut

Shine: roughly 20-225% % (at 60°)

Destination: interior

Application / Painting: brush
spray gun
roller (lacquer roller, roller with short bristles, polyamide textured 6mm roller)

Density: 1.30

Coverage: 10-12 m² per liter, depending on surface

Drying time at 20°C: touch dry after 2 hours, re-coat after 6 - 12hours

Washability: washable and wipeable

Conditions of painting: -air and surface temperature between 10°C and 25°C
-relative humidity: interior maximum 60%.

Thinners / Dilution: ready to use – dilute with water if applying with spray gun (5-10%)

To clean tools: water

Colours: 128 colours

Availability: 0.75, 2.5 and 5 liters cans

Instructions for use

Preparation of surfaces:

The state and the preparation of surfaces should conform to professional uses specifications (DTU 59-1 in France).

"ARGILE laque satinée intérieure" is to be used after the following preparations: cleaning, degreasing, sand-papering... on the following interior and exterior surfaces:

- plaster, plaster covered by a sheet of carton, water based filler, apply a first coat of "ARGILE sous couche de préparation"
- on particularly absorbent, dusty or chalky surfaces, or on repaired or filled surfaces, apply a solvent based primer.
- on already painted surfaces, check the adherence of the previous coat, remove the parts that are not adhesive, wash and sand-paper the area. Also carry out any filling in that are necessary.
- on old matt paint, especially in the case of ceilings, apply a first coat of "ARGILE sous couche de préparation"
- on shiny or silky surfaces, clean and then sand-paper thoroughly, apply one coat of "Argile primaire universel"
- with non-ferrous metals, or if the surface or the adherence is poor (PVC, hard plastic...), clean and then sand-paper. Apply one coat of "Argile primaire universel"
- with untreated wood, degrease, clean, sand-paper, and then apply a first coat of "ARGILE primaire universel"
- the degreasing of wood should be done with specific degreasing liquid (trichloroethylene, acetone...)
- with covered wood (with paint, stains, or varnish...) remove the non-adhesive parts and sand-paper them, apply one coat of "Argile primaire universel"
- on derivatives of wood (melamine, laminated wood...), clean and sand-paper, apply one coat of "Argile primaire universel"
- for furniture, remove all traces of polish or wax, sand-paper it thoroughly and scour off any old varnish. Then apply a coat of "ARGILE primaire universel", followed by two coats of "ARGILE Laque Satinée Intérieure"
- on old wall paper or wall covering , apply a coating of "ARGILE primaire universel", then sand-down regularly if you notice any straightening *of the fibers*.
- if any old wall covering have been stripped off, be sure to remove any traces of glue with the appropriate products

Application

Stir well manually before using the product

Apply two coats of "ARGILE laque satinée intérieure" with brush, spray gun or roller

On smooth surfaces, those are perfectly prepared use a polyamide textured 6mm roller. On other surfaces, use a polyamide textured 6-8mm textured roller

Using a brush will obtain a taut appearance

When using a spray gun, dilute the product with water by 5-10%

Upkeep/Maintenance

"ARGILE laque satinée intérieure" can be cleaned with a warm sponge. Avoid aggressive scrubbing. Use soft detergents if necessary.

Health and Safety

Keep out of reach of children. Use only in well ventilated areas.

In accordance with the development of our knowledge and of our techniques, this information sheet may be modified over the course of time.