

**ARGILE SATIN COUVRANT**

Description : « ARGILE Satin couvrant » is a satin acrylic paint , water based , garnishing, covering, and easy and pleasant to apply.

Destination : all standard interior surfaces untreated or already painted (walls, doors, woodwork, old paints, plastic , non ferrous metal etc...).

Advantages : - without smell  
- very low VOC rate  
- garnishing,  
- very good opacity  
- tools can be cleaned with water  
- easy to apply

COV : - Limit value for this product (cat A/a : 30 g/l). This product contains max 15 g/L of VOC.

Air Emission : very low solvent waste (class A+ according ISO 16000 norm).

**CHARACTERISTICS**

Aspect : Satin, finely structured ,regular aspect.

Destination : Inside use

Application : Brush  
Spray gun  
Roller (Textured 7 or 12 mm polyamide roller by example)

Density : 1,4

Coverage : 7 to 9 m<sup>2</sup> per liter, according to substrate

Drying time at 20°C : touch dry after 2 hours, recoatable after 6 hours.

Washability : washable

Necessary conditions for painting: -air and surface temperature between 10°C and 25°C  
-relative humidity: maximum 60%

Thinners / Dilution: ready to use – dilute with water on particularly absorbent surfaces or if applying with spray gun (5- 10 %)

Cleaning tools : water

Colours: 184 colours

Availability: 0.75, 2.5, and 5 liters cans

## **INSTRUCTION FOR USE**

Destination :

« Argile satin couvrant » can be used inside, upon all kinds of supports. It is garnishing, and can be used even on non regular or well prepared substrates.

Preparation of surfaces:

The state and the preparation of surfaces should conform to professional uses specifications (DTU 59-1 in France). Surfaces should be dry, the room well-ventilated, and air temperature between 10 and 25°C.

"ARGILE satin couvrant" is designed to be used on all types of interior surfaces (walls, woodwork) after the pre-application procedures have been carried out (cleaning, sand-papering...)

- on plaster, *plaster* recoated by a sheet of carton, water based filler, apply a first coat of "ARGILE sous couche de preparation"
- on already painted surfaces, check the adherence of the previous coat; remove the parts that are not adherent, then wash and sand-paper the area. Also carry out any filling in and repairing that are necessary, apply a first coat of "Argile sous couche de preparation"
- on shiny and hard paint, sand , apply a first coat of "Argile primaire universel".
- if covering a matt or absorbent paint , apply as undercoat "ARGILE sous couche de preparation"
- on non-ferrous metals and other surfaces where adherence is difficult (hard plastic, PVC...), after sanding apply a coat of "ARGILE primaire universel"
- on ferrous metals, use an appropriate anti rust primer (consult us)
- on untreated wood, after degreasing and sanding apply a first coat of "ARGILE primaire universel"
- when degreasing wood, use an appropriate liquid degreaser

- on coated wood (varnish, paint, paint), remove any non-adherent parts, and after sand-papering apply a first coat of "ARGILE primaire universel"
- with derivatives of wood (melamine, laminated...), after sand-papering apply an undercoat of "ARGILE primaire universel"
- with furniture, remove all traces of polish, sand-paper thoroughly or scour off any old varnish. Then apply a coat of "ARGILE primaire universel", followed by two coats of "ARGILE satin couvrant". Protect any particularly exposed surfaces (to rubbing, bumps, or liquid etc...) with one or two coats of an appropriate varnish (consult us)
- on old wall covering or old adherent coatings, apply a coating of "ARGILE primaire universel", then sand-down regularly if you notice any straitening of fibers.
- if any old coatings have been stripped off, be sure to remove any traces of glue with the appropriate products. Apply one coat of "Argile primaire universel"

### **Application**

Mix well manually before using the product

Apply two coats of "ARGILE satin couvrant" with brush, spray gun or roller

Use a textured polyamide 12mm roller, or a 7mm polyamide roller on small and smooth surface (doors , furnitures ...)

In case of applying the paint with a spray gun, dilute it by 5-10% of water

### **Maintenance**

"Argile satin couvrant" can be washed

### **Health and Safety**

Keep out of reach of children. Use only in well ventilated areas

Consult our technical data sheet

In accordance with the development of our knowledge and of our techniques, this information sheet may be modified over the course of time.